


Z series



Rating / 規格	20(4)A 250VAC EN61058-1 15A 125VAC or 250VAC UL 1054 1/2A 125VDC 1/4A 250VDC 1/8HP 125VAC 1/4HP 250VAC
Contact Resistance / 接觸電阻	15mΩ max. (initial)
Insulation Resistance / 絕緣電阻	100MΩ min. (at 500VDC)
Dielectric Strength / 耐電壓	AC 1000V (50/60Hz for 1minute)
Electrically Life / 電氣壽命	100,000 operation min.



Z15G1300

Z15G1301



Z15G1303



Z15G1305



Z15G1701



Z15G1702



Z15G1306



Z15G1307



Z15G1308



Z15G1318



Z15G1703



Z15G1704



Z15G1744



ZP15G1306



TERMINAL ENCLOSURES
AA8000

VT series



Rating / 規格	16(4)A 250V AC, IEC 61058-1, UL1054
Contact Resistance / 接觸電阻	15mΩ max. (initial)
Insulation Resistance / 絕緣電阻	100MΩ min. (at 500VDC)
Dielectric Strength / 耐電壓	AC 1000V (50/60Hz for 1minute)
Electrically Life / 電氣壽命	100,000 cycles min



VT1600




VT1601



VT1602



VT1603



VT1604



VT1605



VT1606


VS series



Rating / 規格	10A 125V AC or 250V AC, UL1054
Contact Resistance / 接觸電阻	15mΩ max. (initial)
Insulation Resistance / 絕緣電阻	100MΩ min. (at 500VDC)
Dielectric Strength / 耐電壓	AC 1000V (50/60Hz for 1minute)
Electrically Life / 電氣壽命	100,000 cycles min



VS10N00



VS10N01



VS10N02



VS10N03



VS10N04



VS10N05



VS10N06



VAQ-4



VAQ-5



AB5151



AB6161