

cylindrical cartridge fuses

NNN



Dimensions (p. 387)

Pack	Cat. Nos.	Cylindrical miniature 5 x 20		
		Type F (fast acting) fuse Ceramic body Conform to IEC 60127-2 For use with sensitive equipment, transformers, Viking 3 terminals etc.		
		Rating (Amps)	Voltage ~ (Volts)	Rupture capacity (Amps)
10	0102 02	0.2		
10	0102 05	0.5		
10	0102 06	0.63		
10	0102 10	1		
10	0102 12	1.25		
10	0102 16	1.6		
10	0102 20	2	250	1500
10	0102 25	2.5		
10	0102 30	3.15		
10	0102 50	5		
10	0102 63	6.3		
10	0102 96 ⁽¹⁾	10	250	500

Pack	Cat. Nos.	Cylindrical type gG			
		Conform to BS EN 60269-1, IEC 60269-1			
		Without indicator	Rating (Amps)	Voltage ~ (Volts)	Breaking capacity (Amps)
		8.5 x 31.5			
10	0123 01		1		
10	0123 02		2		
10	0123 04		4		
10	0123 06		6		
10	0123 08		8	400	20 000
10	0123 10		10		
10	0123 12		12		
10	0123 16		16		

Pack	Cat. Nos.	Cylindrical type gG industrial			
		HRC (high rupturing capacity) Conform to BS EN 60269-1 and 2 (BS 88) IEC 60269-1, 2 and 2-1 Bureau Veritas approved			
		Without indicator	Rating (Amps)	Voltage ~ (Volts)	Breaking capacity (Amps)
		10 x 38			
10	0133 94		0.5		
10	0133 01		1		
10	0133 02		2		
10	0133 04		4		
10	0133 06		6	500	100 000
10	0133 08		8		
10	0133 10		10		
10	0133 12		12		
10	0133 16		16		
10	0133 20		20		
10	0133 25		25		
		14 x 51			
10	0143 02		2		
10	0143 04		4		
10	0143 06		6		
10	0143 10		10	500	100 000
10	0143 16		16		
10	0143 20		20		
10	0143 25		25		
10	0143 32		32		
10	0143 40		40		
10	0143 50		50		
		22 x 58			
10	0153 04		4		
10	0153 06		6		
10	0153 10		10		
10	0153 16		16		
10	0153 20		20		
10	0153 25		25	500	100 000
10	0153 32		32		
10	0153 40		40		
10	0153 50		50		
10	0153 63		63		
10	0153 80		80		
10	0153 96		100	400	
10	0153 97		125		

Pack	Cat. Nos.	Neutral links	
10	0123 00	8.5 x 31.5	
10	0133 00	10 x 38	
10	0143 00	14 x 51	
10	0153 00	22 x 58	

Note : Numbers refer to physical size of fuse i.e. 10 x 38 means Ø 10 mm x 38 mm length

Fuses with strikers are available on special request in specific ratings
Minimum pack quantities apply

For other ratings and types

Contact us on 0845 605 4333

(1) Overrating not described by standards